

Series Diaphragm Operated Pressure Switches

Visible Setpoint Adjustment, Compact









1-1/16 Ø7/8 [22.23] 15/16 KNOCK-OUT HOLE [26.99] \5-1/16 [128.69]-[23.81] 7/8 [22.23] / CONDUIT HOLE \4-11/16 [119.36]- 3-1/8 [79.71] 2-13/32 [61.13] [2]01/4 [101.60] [6.35] MOUNTING HOLE WITH SEALING WIRE 1-13/16 1/4 NPT ADJUSTMENT [46.05] 2-7/8 1-7/16 SCREW WITH __4-1/8 [104.78]___ SEALING WIRE [73.03] [36.52]

Reliable and convenient, Series AP pressure switch is a compact switch for instrument air or other low pressure applications. Visible set point and external adjustment add convenience. Used on air, noncorrosive gas or liquid service compatible with wetted parts. Unit also available in weatherproof and explosion-proof housing.

	Switch*				Max. Press.
	Туре		Switch Deadband		psig
Model	SPDT	Ranges	Low	High	(bar)
AP-153-33	Mercury	10 in vac-50 in w.c.	5 in w.c.	6 in w.c.	15
		(2.5-12.4 kPa)	(1.2 kPa)	(1.49 kPa)	(1.03)
AP-153-37	Mercury	1-30 psig	0.4 psig	0.75 psig	60
		(.07-2.1 bar)	(0.03 bar)	(0.05 bar)	(4.14)
AP-153-39	Mercury	10-125 psig	2 psig	6 psig	160
		(.69-8.6 bar)	(0.14 bar)	(0.04 bar)	(11.0)
AP-7021-153-33	Snap	10 in vac50 in w.c.	8 in w.c.	10 in w.c.	15
		(2.5-12.4 kPa)	(2.0 kPa)	(2.49 kPa)	(1.03)
AP-7021-153-37	Snap	1-30 psig	0.75 psig	1.5 psig	60
		(.07-2.1 bar)	(0.05 bar)	(0.10 bar)	(4.14)
AP-7021-153-39	Snap	10-125 psig	3 psig	7 psig	160
		(.69-8.6 bar)	(0.21 bar)	(0.48 bar)	(11.0)

*Mercury switch units are not CE approved.

SPECIFICATIONS

Wetted Materials: Nvlon reinforced Buna-N and steel, PTFE and 316 SS optional.

Temperature Limits: -30 to 150°F (-35 to 66°C).

Pressure Limit: See model chart. Enclosure Rating: General purpose. Weatherproof and explosion-proof optional.

Switch Type: SPDT mercury switch or SPDT snap switch. Other switch types available.

Electrical Rating: Mercury switch: 4 A @ 120 VAC/DC, 2 A @ 240 VAC/DC; Snap switch: 15 A @ 120 VAC. 8 A @ 240 VAC, 0.5 A @ 120 VDC, 0.25 A @ 240 VDC

Electrical Connections: Screw terminal.

Conduit Connection: 7/8" (22.23 mm) hole for 1/2" (12.7 mm) conduit hub. Process Connection: 1/4" female

NPT.

Mounting Orientation: Vertical for mercury switch models, any position for snap switch models.

Set Point Adjustment: External screw. Weight: General purpose: 2 lb (0.9

Deadband: See model chart. Agency Approvals: CE, FM, UL. For FM consult factory. (Mercury switch units are not CE approved.)