




Series
DSGT

Digital Indicating Transmitter

±0.25% Full-Scale Accuracy



The Series DSGT Digital Indicating Transmitter is a versatile multi-function process gage that features an excellent 0.25% full-scale accuracy. This all-in-one digital gage package is designed to reduce installation costs, instrument cost, and save space where an application requires a gage, transmitter, and switches. The Series DSGT gage comes standard with a loop-powered 4 to 20 mA transmitter.

The Series DSGT gage is enclosed in a durable fiberglass reinforced thermoplastic case that is designed to meet NEMA 4 (IP56) requirements. The gage features a menu-driven display for easy customization. User selectable features include 12 engineering units of measure, password protected calibration and disable functions, as well as an adjustable bar graph and update/dampening rates.

Model*	Range (psig)	Model*	Range (psig)
DSGT-101-C0S	30" Hg-0-15	DSGT-109-C0S	0-300
DSGT-102-C0S	30" Hg-0-30	DSGT-110-C0S	0-600
DSGT-104-C0S	0-30	DSGT-112-C0S	0-1000
DSGT-105-C0S	0-60	DSGT-116-C0S	0-5000
DSGT-106-C0S	0-100	DSGT-117-C0S	0-8000
DSGT-107-C0S	0-160	DSGT-118-C0S	0-10000
DSGT-108-C0S	0-200		

SPECIFICATIONS

GAGE SPECIFICATIONS

Service: Compatible, non-combustible liquids & gases.

Wetted Materials: 17 to 4 stainless steel sensor, 316 SS socket.

Housing Materials: Fiberglass reinforced thermoplastic case.

Accuracy: 0.25% full-scale (includes linearity, hysteresis, repeatability).

Pressure Limit: 2 x full-scale range.

Process Connection: 1/2" male NPT.

Display: 5 digit (0.88" high).

TRANSMITTER SPECIFICATIONS

Power Requirements: 12-36 VDC (loop powered).

Memory Back Up Supply: (2) C alkaline batteries, installed functional, user replaceable.

Output Signal: 4-20 mA.

Response Time: 100 ms.

Temperature Limits: 14 to 140°F (-10 to 60°C).

Thermal Effects: 0.04% full-scale/°F.

Electrical Connections: 3 ft flying leads.

Loop Resistance: DC; 0-1090 Ω max.

Set Point Adjustments: Adjustable through menu selections.

Weight: 1.45 lb (.66 kg).

Agency Approvals: CE.

OPTION

For NIST traceable calibration certificate, use order code NISTCAL-PT1.

PRESSURE

Single Pressure Gages/Switches/
Transmitters, Digital