SERIES 657

RELATIVE HUMIDITY/TEMPERATURE TRANSMITTER

Dual Channel Design for Simultaneous 4 to 20 mA Output Signals

657





657C



The **SERIES 657** Transmitters provide two 4 to 20 mA channels to produce separate output signals for both relative humidity and temperature. These devices deliver ±2% accuracy for humidity and ±1°F for temperature measurements. Stainless steel probe can be easily mounted to most ductwork using either of the two optional kits below.

FEATURES/BENEFITS

- Polymer film humidity and thin film RTD temperature sensors offer highly reliable and stable measurements.
- Remote mount housing offers installation flexibility (657-1)
- Rugged die-cast aluminum housing is great for industrial applications (657C-1)

APPLICATIONS

- Cleanroom monitoring
- HVAC/building control monitoring

MODEL CHART		
Model	**Description**	**Price**
657-1	RH/temperature transmitter	**$288.00**
657C-1	RH/temperature transmitter - conduit housing	**319.00**

ACCESSORIES		
Model	**Description**	**Price**
A-158	Split flange	**$13.75**
A-159	Mounting gland	**28.00**

A-158

A-159

SPECIFICATIONS

Service: Dry clean air.
Range: Relative humidity: 0 to 100%; Temperature: 32 to 212°F (0 to 100°C).
Accuracy: Relative humidity: ±2% (10 to 90% RH), ±3% (0 to 10% and 90 to 100% RH); Temperature ±1°F (0.5°C).
Temperature Limits: 32 to 140°F (0 to 60°C).
Pressure Limits: 1 psi (.07 bar).
Compensated Temperature Range: 32 to 140°F (0 to 60°C).
Power Requirements: 10 to 35 VDC.
Output Signal: 2 channels each 4 to 20 mA. Loop powered on the RH channel.
Electrical Connections: 4 screw type terminals.
Mounting Orientation: Mount in any position.
Probe: 657-1: Stainless steel 5/16″ x 10″ (0.8 x 25.4 cm); 657C-1: 5/16″ x 9-1/10″ (0.8 x 23.1 cm).
Weight: 657-1: 5.5 oz (156 g); 657C-1: 10 oz (284 g).

OPTION		
To order add suffix:	**Description**	**Price**
-NIST	NIST traceable humidity calibration certificate	**$121.00**
Example: 657C-1-NIST		