


TWO-PIECE STAINLESS STEEL BALL VALVE

Full Port, 1000 psig (69 bar)



Dimensions (in)							
A (Ref)	B (Ref)	C (Ref)	D (NPT)	E (UNC)	F (+.015)	G (+.015)	H (+.015)
1/4"	2.165	4.055	1/4"	(2) 3/16-24	0.500	1.102	N/A
3/8"	2.165	4.055	3/8"	(2) 3/16-24	0.500	1.102	N/A
1/2"	2.559	5.236	1/2"	(2) 3/16-24	0.500	1.102	N/A
3/4"	2.992	5.236	3/4"	(2) 3/16-24	0.882	1.378	N/A
1"	3.465	6.024	1"	(2) 3/16-24	0.882	1.378	N/A
1-1/4"	3.976	6.024	1-1/4"	(2) 1/4-20	1.000	1.500	N/A
1-1/2"	4.331	7.520	1-1/2"	(2) 1/4-20	1.000	1.500	N/A
2"	4.882	7.520	2"	(4) 1/4-20	1.000	1.500	2.000
2-1/2"	6.299	9.724	2-1/2"	(4) 1/4-20	1.382	2.165	2.764
3"	6.929	9.724	3"	(4) 1/4-20	1.382	2.165	2.764

The **SERIES BV2** is the economical choice for high quality, SS ball valves for use in chemical, petrochemical, pulp and paper and general applications. The Series BV2 body and endcaps are constructed of investment cast SS, while stem is 316 SS. Seats and body seals are 15% glass reinforced PTFE providing broad media compatibility and bubble tight shutoff to 1000 psig (69 bar). Internally loaded, blowout-proof stem provides safety in the event of overpressure. Full port design allows for maximum Cv with minimal pressure drop. Integral actuator mounting pads allows for ease of automation.

SPECIFICATIONS

End Connections: Female NPT.

Pressure Limits: 1000 psi (69 bar) WOG, 150 psi (10.3 bar) SWP.

Wetted Materials: Body, ball, end cap: CF8M SS; Stem: 316 SS; Seat, thrust washer: RTFE; End gasket, stem packing: PTFE.

Temperature Limits: -20 to 450°F (-29 to 232°C).

MODEL CHART					
Model	Size	Price	Model	Size	Price
BV2M100	1/4"	\$27.50 [Ⓟ]	BV2M105	1-1/4"	\$75.00 [Ⓟ]
BV2M101	3/8"	24.75 [Ⓟ]	BV2M106	1-1/2"	103.00 [Ⓟ]
BV2M102	1/2"	30.75 [Ⓟ]	BV2M107	2"	149.00 [Ⓟ]
BV2M103	3/4"	39.00 [Ⓟ]	BV2M108	2-1/2"	300.00 [Ⓟ]
BV2M104	1"	66.00 [Ⓟ]	BV2M109	3"	388.00 [Ⓟ]

[Ⓟ] Items are subject to Schedule B discounts.