


**Dwyer**


SERIES SRC | W.E. ANDERSON™ BY DWYER

# SOLENOID REPLACEMENT COILS

For the Series SSV and SBSV Solenoid Valves



Models SRC-X180X &amp; SRC-X280X



Models SRC-XXS0X

The **Series SRC Solenoid Replacement Coils** electrically operate the SSV and SBSV solenoid valves. When the solenoid coil receives an electrical input signal it acts upon the valve, changing its state. These coils are field replaceable with their compatible solenoid valves and come in a wide range of voltages.

**FEATURES/BENEFITS**

- Field replaceable

**APPLICATIONS**

- Replacement coils for SSV and SBSV solenoid valves

**SSV COMPATIBLE COILS**

Model	Voltage	50 Hz (VA)		60 Hz (VA)		DC (W)
		Inrush	Holding	Inrush	Holding	
<b>SRC-D1B0P</b>	220 VAC	82	33	82	28	-
<b>SRC-D2B0P</b>	110 VAC	82	33	82	28	-
<b>SRC-D3B0P</b>	24 VAC	72	29	72	25	-
<b>SRC-D4B0P</b>	24 VDC	-	-	-	-	32

**Note:** Consult factory for 220 VAC, 24 VAC and 24 VDC.**SPECIFICATIONS****Compatible Valves:** SSV or SBSV.**Power Requirements:** 220 VAC, 110 VAC, 24 VAC or 24 VDC.**Electrical Connections:** DIN connection.**Enclosure Rating:** NEMA 13 (IP54).**Power Consumption:** See table.**Agency Approvals:** CE.**SBSV COMPATIBLE COILS**

Model	Voltage	50 Hz (VA)		60 Hz (VA)		DC (W)
		Inrush	Holding	Inrush	Holding	
<b>SRC-D1S0C</b>	220 VAC	55	22	55	18	-
<b>SRC-D2S0C</b>	110 VAC	55	22	55	18	-
<b>SRC-D3S0C</b>	24 VAC	45	18	45	15	-
<b>SRC-D4S0C</b>	24 VDC	-	-	-	-	13

**Note:** Consult factory for 220 VAC, 24 VAC and 24 VDC.