

INDUSTRIAL PRESSURE TRANSMITTERS

Complete Offering of Ranges, Connections and Outputs



626/628 Pressure Transmitters
with General Purpose Housing (-GH)



626/628 Pressure Transmitters
with Conduit Box Housing (-CB) and LCD display



*Please see our website for dimensional drawings.

The **Series 626 Industrial Pressure Transmitters** possess a highly precise 0.25% full scale accuracy piezo-resistive sensor contained in a compact, rugged, NEMA 4X (IP66) stainless steel general purpose housing or cast aluminum conduit housing. The **Series 628 Industrial Pressure Transmitters** are ideal for OEMs with 1% full scale accuracy sensors. The corrosion resistant 316L stainless steel wetted parts allow the Series 626 and 628 transmitters to measure the pressure in a multitude of processes from hydraulic oils to chemicals. The Series 626 and 628 are available in absolute and pressure ranges with a variety of optional outputs, process connections and electrical terminations to allow you to select the right transmitter for your application.

FEATURES/BENEFITS

- NEMA 4X rated enclosure provides protection in harsh environments permitting outdoor monitoring or in areas where dust and particulate matter exists
- Robust 316 SS oil filled sensor provides shock and vibration resistance insuring stability in controlling pressure for process applications
- A wide range of models and connections that can meet pressure measurement specifications from low to very high

APPLICATIONS

- Compressors
- Pumping systems
- Irrigation equipment
- Hydraulic
- Industrial process monitoring

SPECIFICATIONS

Service: Compatible gases and liquids.

Wetted Materials: Type 316L SS.

Accuracy: 626: 0.25% FS; 626: 0.20% RSS; 628: 1.0% FS; 628: 0.5% RSS; 626 Absolute Ranges: 0.5% FS; 626 absolute ranges: 0.30% RSS. (Includes linearity, hysteresis, and repeatability.)

Temperature Limit: 0 to 200°F (-18 to 93°C).

Compensated Temperature Range: 0 to 175°F (-18 to 79°C).

Thermal Effect: ±0.02% FS/°F (includes zero and span).

Pressure Limits: See table.

Power Requirements: 10 to 30 VDC (for 4 to 20 mA, 0 to 5, 1 to 5, 1 to 6 VDC outputs); 13 to 30 VDC (for 0 to 10, 2 to 10 VDC outputs); 5 VDC ±0.5 VDC (for 0.5 to 4.5 VDC ratio-metric output), 10 to 35 VDC (for 4 to 20 mA with -CB option); 13 to 35 VDC or isolated 16 to 33 VAC (for selectable output with -CB option).

Output Signal: 4 to 20 mA, 0 to 5 VDC, 1 to 5 VDC, 0 to 10 VDC, or 0.5 to 4.5 VDC, or selectable 0 to 5, 1 to 5, 0 to 10, 2 to 10 VDC for -CB option.

Response Time: 300 ms.

Loop Resistance: 0 to 1000 Ohms max. $R_{max} = 50 (V_{ps}-10)$ Ohms (4 to 20 mA output), 0 to 1250 Ohms max. $R_{max} = 50(V_{ps}-10)$ Ohms (4 to 20 mA output with -CB option), 5K Ohms (0 to 5, 1 to 5, 1 to 6, 0 to 10, 2 to 10, 0.5 to 4.5 VDC output).

Stability: 1.0% FS/year (Typ.).

Current Consumption: 38 mA maximum (for 4 to 20 mA output); 10 mA maximum (for 0 to 5, 1 to 5, 1 to 6, 0 to 10, 2 to 10, 0.5 to 4.5 VDC output); 140 mA maximum (for all 626/628/629-CH with optional LED).

Electrical Connections: Conduit Housing (-CH): terminal block, 1/2" female NPT conduit; General Purpose Housing (-GH): cable DIN EN 175801-803-C.

Process Connection: 1/4" male or female NPT and BSPT.

Enclosure Rating: NEMA 4X (IP66).

Mounting Orientation: Mount in any position.

Weight: 10 oz (283 g).

Agency Approvals: CE, NSF, UL.

INDUSTRIAL PRESSURE TRANSMITTERS

Complete Offering of Ranges, Connections and Outputs

MODEL CHART									
Example	626	-00	-CH	-P1	-E1	-S1	-AT	626-00-CH-P1-E1-S1-AT	Price
Accuracy	626							0.25% full scale accuracy	\$128.00
	628							1.0% full scale accuracy	84.50
Range		00						0 to 15 psia [Ⓞ]	+25.00
		01						0 to 30 psia [Ⓞ]	+25.00
		02						0 to 50 psia [Ⓞ]	+25.00
		03						0 to 100 psia [Ⓞ]	+25.00
		04						0 to 200 psia [Ⓞ]	+25.00
		05						0 to 300 psia [Ⓞ]	+25.00
		06						0 to 5 psi	-
		07						0 to 15 psi	-
		08						0 to 30 psi	-
		09						0 to 50 psi	-
		10						0 to 100 psi	-
		11						0 to 150 psi	-
		12						0 to 200 psi [Ⓞ]	-
		13						0 to 300 psi [Ⓞ]	-
		14						0 to 500 psi [Ⓞ]	-
		22						0 to 600 psi [Ⓞ]	-
		15						0 to 1000 psi	-
		16						0 to 1500 psi [Ⓞ]	+25.00
		18						0 to 3000 psi	+25.00
		19						0 to 5000 psi	+25.00
		26						0 to 8000 psi	+25.00
		67						0 to 0.5 bar	-
		71						0 to 2.5 bar	-
		75						0 to 10 bar	-
		81						0 to 40 bar	-
Housing			CB					Conduit box housing	+35.75
			GH					General purpose housing	-
Process Connection				P1				1/4" male NPT	-
				P2				1/4" female NPT	-
				P3				1/4" male BSPT	-
				P5				1/4" female SAE with refrigerant valve depressor [Ⓛ]	-
				P9				1/2" male NPT [Ⓞ]	-
Electrical Connection					E1			Cable gland with 3' of prewired cable	-
					E3			Cable gland with 9' of prewired cable	+5.70
					E4			DIN EN 175801-803-C [Ⓞ]	+5.00
					E5			1/2" female NPT conduit [Ⓞ]	-
					E6			M-12 4 pin connector-UL [Ⓞ]	+12.75
					E8			Packard connector	-
					E9			M-12 4 pin connector non-UL	-
Signal Output						S1		4 to 20 mA	-
						S2		1 to 5 VDC	-
						S4		0 to 5 VDC	-
						S5		0 to 10 VDC	-
						S7		0.5 to 4.5 VDC [Ⓛ] [Ⓞ]	-
						S8		Selectable 0 to 5, 1 to 5, 0 to 10, 2 to 10 VDC [Ⓞ]	-
Options							AT	Aluminum tag	+14.25
							LCD	LCD indication [Ⓞ]	+100.00
							NIST	NIST traceable certificate	+139.00
							NW	NSF/ANSI 61/372 certified	+59.00

ⓁAvailable with -GH housing only, NEMA 4 (IP65) ⓄAvailable with -CB housing only ⓄPower requirement: 5 VDC ±10%
 ⓄAvailable with -GH housing only ⓄAbsolute ranges for 626 are 0.5% FS accuracy and for 628 are 2% FS accuracy
 ⓄUL listed pump controllers, fire-component - See online certificate for information and limitations

Note: Bar and absolute ranges are only available with -GH housing.

PRESSURE LIMITS							
Range Number	Pressure Range	Maximum Pressure (psig)	Over Pressure (psig)	Range Number	Pressure Range (psig)	Maximum Pressure (psig)	Over Pressure (psig)
00	0 to 15 psia	30	45	12	0 to 200	400	1000
30	15 to 0 psia	30	45	13	0 to 300	600	1500
06	0 to 5 psig	10	50	14	0 to 500	1000	2500
07	0 to 15 psig	30	150	15	0 to 1000	2000	5000
08	0 to 30 psig	60	300	16	0 to 1500	3000	5000
09	0 to 50 psig	100	300	18	0 to 3000	6000	7500
10	0 to 100 psig	200	500	19	0 to 5000	7500	10000
11	0 to 150 psig	300	750	26	0 to 8000	10000	12000

ACCESSORIES		
Model	Description	Price
A-164	16.4' (5 m) cable with M-12 4-pin female connector	\$29.25
A-62X-LCD	Field-upgradeable LCD	133.00
A-960	3' packard cable	16.00
A-961	9' packard cable	18.25
A-962	20' packard cable	19.25