

The Series P3 Polypropylene Flow Switches fit almost any piping requirements with compatible liquids. Choose the inlet and outlet port to be 3/8" male NPT or 1/4" male "Quick Disconnect" then select a quick disconnect acetal adapter for straight through flow or with a shut off valve.

FEATURES/BENEFITS

- · Piston design incorporates a hermetically sealed SPST magnetic reed switch
- · Easy integration to existing piping with a variety of fitting options
- · Selectable shut off valve will stop line flow when the adapter is removed from the switch
- · Economical design

MODEL CHART		
Model	Connection	Actuation Set Point
P3-31	3/8" NPT	0.25 GPM (.95 LPM)
P3-32	3/8" NPT	0.50 GPM (1.89 LPM)
P3-33	3/8" NPT	1.0 GPM (3.79 LPM)
P3-34	3/8" NPT	1.5 GPM (5.68 LPM)
P3-35	3/8" NPT	2.0 GPM (7.57 LPM)
P3-41	Quick disconnect	0.25 GPM (.95 LPM)
P3-42	Quick disconnect	0.50 GPM (1.89 LPM)
P3-43	Quick disconnect	1.0 GPM (3.79 LPM)
P3-44	Quick disconnect	1.5 GPM (5.68 LPM)
P3-45	Quick disconnect	2.0 GPM (7.57 LPM)

APPLICATIONS

- · Pure water equipment
- Filter life monitoring
- · Heat exchangers
- Cooling applications

SPECIFICATIONS Service: Compatible liquids. Electrical Rating: Wetted Materials: Housing: Electrical Connect Polypropylene: Piston: PPS composite; polymeric wire lead	.08 A @ 120 VAC.
Wetted Materials: Housing: Electrical Connect	.08 A @ 120 VAC.
5	
Polypronylene: Piston: PPS composite: polymeric wire lead	tion: 24" (60.96 cm),
polyhene, i iston. i i o composite, polyhene wie lead	ds, 22 AWG.
Spring: 316 SS; O-ring: Fluorocarbon. Process Connect	ion: 3/8" male NPT or
Temperature Limits: 0 to 212°F (-18 to 1/4" quick disconne	ect.
100°C). Mounting Orienta	tion: Any position. Set
Pressure Limits: 125 psig (8.6 bar) @ points shown are b	ased on vertical, inlet
70°F (21°C), 50 psig (3.4 bar) @ 212°F down position.	
(100°C). Required Filtratio	n: 100 microns or
Accuracy: 20% of set point. better.	
Repeatability: ±1%. Weight: 5 oz (0.14	kg).
Switch Type: SPST, NO.	

ADAPTERS		
Model	Connection	
P3-801	Quick disconnect straight through 1/4" NPT	
P3-802	Quick disconnect straight through 1/4" BSPT	
P3-804	Quick disconnect straight through 3/8" BSPT	
P3-807	Quick disconnect straight through 1/4" ID tubing	
P3-901	Quick disconnect straight through 1/4" NPT w/shut-off valve	
P3-902	Quick disconnect straight through 1/4" BSPT w/shut-off valve	
P3-907	Quick disconnect straight through 1/4" ID tubing w/shut-off valve	