


IN-LINE FLOW TRANSMITTER

Local Flow Indication, Unrestricted Mounting, 4-20 mA, 0-5 V, and 1-5 V Output

CALIBRATION SERVICES AVAILABLE



The **Series HFT In-Line Flow Transmitter** provides continuous monitoring of flow rate levels via a direct reading in-line flowmeter with electronics to provide proportional 4-20 mA, 0-5 and 1-5 VDC analog outputs.

FEATURES/BENEFITS

- Provides analog output to monitor application flow and integral direct reading scale to provide local indication of flow rate
- Increased application versatility with no inlet or outlet straight plumbing requirement and can be mounted horizontally, vertically, or inverted
- Outdoor or harsh environment installation capable with rugged cast aluminum construction and NEMA 4X (IP65) enclosure

APPLICATIONS

- Waste water processing
- Lubrication systems
- Process control
- Solar systems
- Drain lines
- Pump testing
- Drive data acquisition devices, meters or analog input cards

MODEL CHART - DUAL SCALE RANGE

Model	Connection Size	Range, Air: SCFM, SLPS	Body Material	Price
HFT-1112	1/4" female NPT	2 to 12, 1 to 5.5	Aluminum	\$872.00 ^(N)
HFT-1123	1/4" female NPT	4 to 23, 2 to 10	Aluminum	872.00 ^(N)

^(N) Items are net priced and are not subject to any discount.

OPTIONS

Use order code:	Description	Price
NISTCAL-FT1	NIST traceable calibration certificate	\$215.00 ^(N)

^(N) Items are net priced and are not subject to any discount.

SPECIFICATIONS

Service: Compatible gases or liquids.
Wetted Materials: Body: Aluminum, brass or 304 SS; Seals: Buna-N or Fluoroelastomer; Magnet: PTFE coated Alnico; Other internal parts: 304 SS.
Viscosity: 500 SSU.
Temperature Limits: 170°F (76°C).
Pressure Limits: Aluminum body: 600 psig (41 bar); Brass body: 3500 psig (240 bar); 304 SS body: 6000 psig (413 bar).
Power Requirements: 12-35 VDC.
Enclosure Rating: NEMA 4X (IP66).
Accuracy: ±2% FS.
Repeatability: ±1% of FS.
Response Time: < 100 ms.
Output Signal: 4-20 mA; 0-5 V; 1-5 V.
Shipping Weight: 1/4 to 1/2" female NPT models: 3 lb (1.4 kg); 3/4 to 1" female NPT models: 4.5 lb (2.0 kg); 1-1/2" female NPT models: 12 lb (5.4 kg).

MODEL CHART

Model	Connection Size	Range, Water: GPM, LPM	Body Material	Price
HFT-2205	1/2" female NPT	0.5 to 5.0, 2 to 19	Brass	\$920.00 ^(N)
HFT-2315	3/4" female NPT	1 to 15, 5 to 55	Brass	1006.00 ^(N)
HFT-2320	3/4" female NPT	2 to 20, 1 to 75	Brass	1006.00 ^(N)
HFT-2440	1" female NPT	4 to 40, 15 to 150	Brass	1006.00 ^(N)
HFT-2550	1-1/2" female NPT	6 to 50, 20 to 190	Brass	1921.00 ^(N)
HFT-3202	1/2" female NPT	.2 to 2, 1 to 8	304 SS	1159.00 ^(N)
HFT-3210	1/2" female NPT	1 to 10, 3 to 3.75	304 SS	1159.00 ^(N)

^(N) Items are net priced and are not subject to any discount.

USA: California Proposition 65

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov