





Series
62000MU

2.5" Stainless Steel Pressure Gage

Brass Wetted Parts, Back Connection with Mounting Bracket



The Series 62000MU Gages have dual english/metric scales with $\pm 1.6\%$ full scale accuracy, and are available in 2.5" dial sizes. Series 62000MU gages are designed with 304 SS housings and brass wetted parts, and includes a back u-clamp connection for panel mounting. Units can withstand ambient temperatures up to 140°F (60°C) and process temperatures up to 248°F (120°C). The 62000MU gages may be easily liquid filled in the field without the need for a separate kit.

Model	Range
62030VMU	0 to 30 in. Hg Vac (-100 to 0 kPa)
62015MU	0 to 15 psi (0 to 100 kPa)
62030MU	0 to 30 psi (0 to 200 kPa)
62060MU	0 to 60 psi (0 to 400 kPa)
62100MU	0 to 100 psi (0 to 700 kPa)
62160MU	0 to 160 psi (0 to 1100 kPa)
62200MU	0 to 200 psi (0 to 1400 kPa)
62300MU	0 to 300 psi (0 to 2000 kPa)

SPECIFICATIONS

Service: Compatible gases and liquids.

Wetted Materials: Brass.

Housing: 304 SS.

Lens: Plexi-glass.

Accuracy: $\pm 1.6\%$ full scale.

Pressure Limits: 130% of full scale.

Temperature Limits:

Ambient: -4 to 140°F (-20 to 60°C);

Process: 248°F max. (120°C max.).

Size: 2-1/2" (63 mm).

Process Connection: 1/4" male NPT.

Enclosure Rating: NEMA 3 (IP55).

Weight: 4.9 oz (0.14 kg).