



Series
677B



Differential Pressure Transmitter

NEMA 4 Enclosure with Integral Mounting Bracket



PRESSURE

Differential Pressure Transmitters



Series 677B Differential Pressure Transmitters are designed to measure pressures as low as 0.1 in. w.c. with $\pm 0.4\%$ accuracy. Use Series 677B for building energy management systems, environmental pollution control, oven pressurization, lab and fume hood control, HVAC and VAV applications. The transmitter features 15 psid overpressure, reverse polarity protection and EMI/RFI protection. Internal regulation permits use with unregulated DC power supplies. The NEMA 4 housing allows for versatile mounting locations and integral mounting tabs simplify installation.

SPECIFICATIONS

Service: Air and non-conductive, non-corrosive gases.

Wetted Materials: 302 SS, glass, nickel, silicone rubber and brass.

Accuracy: $\pm 0.4\%$ FS* at room temperature.

*RSS includes non-linearity, hysteresis and non-repeatability.

Stability: $\pm 1\%$ FS/yr.

Temperature Limits: Operating and Compensated: 0 to 185°F (-18 to 85°C);

Storage: -65 to 220°F (-54 to 105°C).

Pressure Limit: 15 psi (100 kPa).

Thermal Effects: (Includes zero and span) $< 0.028\%$ FS/°F, 0 to 185°F (-18 to 85°C).

Power Requirement: 16 to 32 VDC.

Output: 4 to 20 mA DC, 2-wire.

Zero and Span Adjustments: Internally accessible potentiometers, noninteractive.

Response Time: Approximately 10 ms.

Max. Loop Resistance: DC: 0 to 800 Ω .

Process Connection: 3/16" OD barbed brass pressure fitting.

Enclosure Rating: NEMA 4 (IP65).

Weight: 11.5 oz (330 g).

Agency Approval: CE.

OPTION

For NIST traceable calibration certificate,

use order code NISTCAL-PT1. **\$135.00^(N)**

Model	Range (in w.c.)	Price	Model	Range (in w.c.)	Price
677B-01	0 to 0.1	\$230.00 ^(B)	677B-08	0 to 25	\$230.00 ^(B)
677B-02	0 to 0.25	230.00 ^(B)	677B-11	0 to ± 0.05	230.00 ^(B)
677B-03	0 to 0.5	230.00 ^(B)	677B-12	0 to ± 0.1	230.00 ^(B)
677B-04	0 to 1	230.00 ^(B)	677B-13	0 to ± 0.25	230.00 ^(B)
677B-05	0 to 2.5	230.00 ^(B)	677B-14	0 to ± 0.5	230.00 ^(B)
677B-06	0 to 5	230.00 ^(B)	677B-15	0 to ± 1	230.00 ^(B)
677B-07	0 to 10	230.00 ^(B)			

^(B) Items are subject to Schedule B discounts.

ACCESSORIES

A-302F-A, 303 SS Static Pressure Tip with mounting flange. For 3/16" ID rubber or plastic tubing. 4" insertion depth. Includes mounting screws **9.10**

A-489, 4" Straight Static Pressure Tip with Flange **6.67**

See page 587 for process tubing options.

^(N) Items are net priced and are not subject to any discount.