




Series  
AD

# Air/Duct Temperature Sensors



**Air/Duct Temperature Sensors** are available in precision platinum, nickel, or balco RTDs and interchangeable NTC thermistors. Sensors are constructed with a hermetically sealed 304 SS sheath and are unaffected by high humidity, contamination, thermal shock or vibration. Flange mount sensors offer low profile mounting and quick installation directly into duct work. Rugged air/duct sensors are ideal for air handlers, fan coil units, ducts, furnaces, freezers, ovens and other through wall temperature sensing applications.

## SPECIFICATIONS

### Accuracy:

Platinum RTD:  $\pm 0.6\%$  @ 32°F (0°C);

Nickel RTD:  $\pm 0.5\%$  @ 32°F (0°C);

Balco RTD:  $\pm 0.1\%$  @ 32°F (0°C);

Thermistors:  $\pm 0.36\%$  F from 32 to 158°F (0 to 70°C).

**Operating Temperature:** -32 to 240°F (-35.5 to 115.5°C).

**Probe Diameter:** 1/4" (6.3 mm).

**Cable Length:** 8" (housing models only).

**Probe Material:** 304 SS.

## Model Coding

Fill in the appropriate numbers or letters to specify the probe of your choice. Fill in all four boxes. If an item or dimension does not apply, fill those boxes with zeros '0'.

