




TEMPERATURE/HUMIDITY SWITCH

Independent Displays, 61 Programmable Parameters, 4 SPST Relays

Humidity Switches



The **Series THC Temperature/Humidity Switch** simultaneously measures and controls temperature and humidity. The unit offers a 3-digit red display for temperature indication and a 3-digit green display indicating humidity. The Series THC is equipped with four independent relays, two for temperature control and two relays for humidity control.

The THC Temperature/Humidity Switch accepts up to two temperature probe inputs (sold separately) and a humidity sensor. A humidity sensor with 0-1 V, 3 V (THC-P sold separately), or 4-20 mA output can be used with the Series THC.

FEATURES/BENEFITS

- Temperature and humidity control in one device
- Password protected parameter settings
- Selectable fail safe status of relay outputs

APPLICATIONS

- Isolation chambers
- Environmental chambers
- Greenhouses
- Beer and wine chillers

MODEL CHART			
Model	Supply Power	Unit	Price
THC-10	115 VAC	°F	\$247.00
THC-11	115 VAC	°C	247.00
THC-20	230 VAC	°F	247.00
THC-21	230 VAC	°C	247.00

SPECIFICATIONS

Measurement Range: Temperature: -58 to 302°F (-50 to 150°C); Humidity: 0 to 100% RH.	Display: Two 3-digit displays. 1/2" digits.
Input: Up to 2 thermistors and 1 humidity sensor.	Resolution: 0.1°.
Output: 4 SPST, 8 A relays @ 250 VAC.	Memory Backup: Nonvolatile memory.
Horsepower Rating (HP): 1/3 HP.	Ambient Operating Temperature: 32 to 158°F (0 to 70°C).
Control Type: ON/OFF direction, direct or reverse acting, neutral.	Storage Temperature: -4 to 176°F (-20 to 80°C).
Power Requirements: 110 or 230 VAC (depending on model).	Weight: 1.17 lb (530 g).
Accuracy: Temperature ±0.5% of probe range; Humidity: 20 to 90%.	Panel Cutout: 5.15" x 3.97" (131 x 101 mm).
	Front Panel Protection: IP64.
	Agency Approvals: CE.

ACCESSORIES

Model	Description	Price
THC-P	Humidity probe, 3 V output, 4 ft (1.2 m) cable	\$54.00 ^(N)
TS-5	Temperature probe, PVC with 5 ft (1.5 m) cable	6.20 ^(N)
TS-6	Temperature probe, metal with 5 ft (1.5 m) cable	7.20 ^(N)
TS-51	Temperature probe, PVC with 10 ft (3 m) cable	8.70 ^(N)
TS-61	Temperature probe, metal with 10 ft (3 m) cable	9.70 ^(N)

^(N) Items are net priced and are not subject to any discount.