



TEMPERATURE/PROCESS INDICATOR

Low Cost, 3-Digit Display, 1% Accuracy



The **Series TID Temperature/Process Indicator** displays temperature or a process value measured by a PTC or NTC thermistor or a 4-20 mA transmitter.

FEATURES/BENEFITS

- Thermistor or transmitter input models available
- 3 digit bright LED

APPLICATIONS

- Panel process indication
- Refrigerators, walk in coolers

| SPECIFICATIONS |
|--|
| Range: -58 to 302°F (thermistor); -999 to 999 counts (4-20 mA). |
| Input: PTC/NTC thermistor or 4-20 mA. |
| Power Requirements: 115 VAC, 230 VAC, 24 VAC/DC. |
| Accuracy: > 1%. |
| Display: 3-digits; red, green or blue display. |
| Resolution: 1° or 0.1 count. |
| Front Panel Rating: IP64 (NEMA 3R). |
| Weight: 2.3 oz (65 g). |
| Agency Approvals: CE, cURus. |

| MODEL CHART | | | | |
|-------------|----------------|--------------|------|---------|
| Model | Input | Supply Power | Unit | Price |
| TID-1110 | PTC thermistor | 115 VAC | °F | \$40.75 |
| TID-1120 | PTC thermistor | 115 VAC | °C | 40.75 |
| TID-1410 | PTC thermistor | 24 VAC/DC | °F | 40.75 |
| TID-3100 | 4-20 mA | 115 VAC | None | 47.50 |
| TID-3200 | 4-20 mA | 230 VAC | None | 47.50 |
| TID-3400 | 4-20 mA | 24 VAC/DC | None | 47.50 |

| ACCESSORIES |
|-----------------------------|
| See page reference 1 below. |