

# Gage Tubing Accessories

## Gage Tubing



## MODELS

**A-200**, Norprene® tubing is useful in a wide range of temperatures from -75 to 275°F (-60 to 135°C) and will not weaken after long term exposure to heat and ozone.

- A-200-1**, 3/16" ID x 5/16" OD, 13 psi maximum pressure @ 73°F (90 kPa @ 23°C); 50' ..... **\$45.00<sup>(N)</sup>**
- A-200-2**, 1/4" ID x 3/8" OD, 10 psi maximum pressure @ 73°F (69 kPa @ 23°C); 50' ..... **.55.00<sup>(N)</sup>**

**A-201**, Rubber latex tubing has less tendency to kink in storage and occupies less space, thus is best for portable work. 3/16" ID, 9' length ..... **.10.00**

**A-202**, Rubber latex tubing. 3/16" ID, lengths to 50' ..... **2.90/ft**

**A-203**, Clear PVC tubing is easily inspected and is therefore best for test applications where a possibility of fluid entering the tubing exists.

1/8" ID x 1/4" OD, lengths to 100' ..... **1.30/ft**

**A-225**, Flexible double column plastic tubing is used with Mark II manometers and the Wind Speed Indicator. Light gray with red color code stripe. 1/8" ID, lengths to 750' ..... **3.10/ft**

**A-204**, Flexible colored vinyl tubing is quickly distinguishable in applications where more than one line is required aiding installation. 3/16" ID x 5/16" OD, lengths to 500'; 45 psi maximum pressure @ 165°F (310 kPa @ 74°C).

- A-204-A**, Opaque Red ..... **.0.86/ft<sup>(N)</sup>**
- A-204-B**, Opaque Blue ..... **.0.86/ft<sup>(N)</sup>**
- A-204-C**, Opaque White ..... **.0.86/ft<sup>(N)</sup>**
- A-204-D**, Opaque Black ..... **.0.86/ft<sup>(N)</sup>**

**A-220**, Clear flexible vinyl tubing is easily inspected, and is therefore best for test applications where a possibility of fluid entering the tubing exists. 3/16" ID x 5/16" OD, lengths to 500'; 45 psi maximum pressure @ 73°F (310 kPa @ 23°C) ..... **2.30/ft**

**A-221**, Clear flexible vinyl tubing is easily inspected, and is therefore best for test applications where a possibility of fluid entering the tubing exists. 1/8" ID x 3/16" OD, lengths to 500'; 40 psi maximum pressure @ 165°F (276 kPa @ 74°C) ..... **2.80/ft**

**A-222**, Clear flexible vinyl tubing is easily inspected, and is therefore best for test applications where a possibility of fluid entering the tubing exists. .240" ID x .375" OD, lengths to 500'; 35 psi maximum pressure @ 73°F (240 kPa @ 23°C) ..... **2.80/ft**

**A-223**, Black polyethylene tubing offers long life, great stability and resistance to corrosion. 1/8" ID x 1/4" OD, 10' length; 200 psi maximum @ 140°F (1379 kPa @ 60°C) ..... **.9.20**

**A-224**, Black nylon tubing is recommended for high temperature and pressure applications. Lengths to 1312 ft; -40 to 248°F (-40 to 120°C).

- A-224-A**, 0.23" ID x 5/16" OD; 362 psi (2500 kPa) working pressure . . **.0.60/ft<sup>(N)</sup>**
- A-224-B**, 0.256" ID x 3/8" OD, 406 psi (2800 kPa) working pressure . . **.0.70/ft<sup>(N)</sup>**

**A-223P**, Black plenum fire retardant polyethylene tubing meets NFPA standard 90A for installation in air-conditioning and ventilating plenum spaces; also used in building automation systems. Lengths to 500', 100 psig maximum pressure @ 75°F (689 kPa @ 24°C).

- A-223P-1**, .17" ID x .25" OD ..... **.0.99/ft<sup>(N)</sup>**
- A-223P-2**, 1/4" ID x 3/8" OD ..... **.1.20/ft<sup>(N)</sup>**

**A-210**, Aluminum tubing is recommended for permanent installations. 1/4" OD, 5' length, 500 psi maximum pressure @ 200°F (3447 kPa @ 93°C) ..... **.6.60**

**A-211**, Aluminum tubing, 1/4" OD, 50' length, 500 psi maximum pressure @ 200°F (3447 kPa @ 93°C) ..... **167.00**

<sup>(N)</sup> Items are net priced and are not subject to any discount. Norprene® is a registered trademark of Saint-Gobain Adhesives, Inc.